



Job __

GARMENT RACKS

Type 304 Stainless Steel and Proven Super Erecta® Construction Throughout.

- Floor-Mountable Upright and Wall Mount versions available.
- · Open wire construction promotes laminar air flow.
- Electro-polished, Type 304 Stainless Steel hangers are included. Hangers are spaced at 3" (76mm)
- Unique hanger capture mechanism provides theft deterrance.
- · Easy to assemble.
- Adjustable stainless steel triangular foot plates provided for floor mounting.
- Available in several sizes to suit your requirements.
- Upright unit is non-conductive, but can be made conductive with the addition of aluminum split sleeves (9986Z).

Floor Mount style is 745/8" tall. Wall Mount style is 71/2" high.





Garment Wire: Wall Mount

Width/Length			Model No.	Approx. Pkd. Wt.		Model No.	Approx. Pkd. Wt.	
(in.)	(mm)	No. of Hangers	Upright	(lbs.)	(kg)	Wall Mount	(lbs.)	(kg)
24x36	610x914	11	GRU2436S	27	12.25	GRW2436S	20	9
24x48	610x1219	15	GRU2448S	36	16.25	GRW2448S	221/2	10.2
24x60	610x1524	19	GRU2460S	45	20.5	GRW2460S	271/2	12.5
24x72	610x1825	23	GRU2472S	54	24.5	GRW2472S	32	14.5





GOWNING BENCH



GOWNING BENCH

Type 304 Stainless Steel, H.D. Super™ Posts and Proven Super Erecta Construction Throughout.

- Heavy-duty, solid top bench provides a sturdy and comfortable gowning fixture. All benches are 18" (457mm) tall.
- Top is manufactured from 14 gauge, Type 304 stainless steel.
- Adjustable stainless steel foot plates provide for floor mounting.
- Available in several lengths to suit your requirements.
- Unit is non-conductive but can be made conductive with the addition of H.D. Aluminum Split Sleeves (9986HZ).

	Width/Length	Approx. Pkd. Wt.
Model No.	(in.) (mm)	(lbs.) (kg)
GB1636S	16x36 406x914	471/2 21.5
GB1648S	16x48 406x1219	55 25
GB1660S	16x60 406x1524	621/2 28.4
GB1672S	16x72 406x1825	70 31.8



All Metro Catalog Sheets are available on our website: www.metro.com

